

Subject: Get more information if GET_COMMAND or GET_COMMAND_ARGUMENT fails
From: Van Snyder
Reference: 03-258r1, section 2.3.2, 04-170, 04-381, WG5/N1626-J3-012

1 **1 Edits**

2 Edits refer to 04-007. Page and line numbers are displayed in the margin. Absent other instructions, a
3 page and line number or line number range implies all of the indicated text is to be replaced by associated
4 text, while a page and line number followed by + (-) indicates that associated text is to be inserted after
5 (before) the indicated line. Remarks are noted in the margin, or appear between [and] in the text.

6 [Editor: Within the STATUS argument paragraph of **13.7.4.1 GET_COMMAND ([COMMAND, 317:17**
7 **LENGTH, STATUS])**, replace “a processor-dependent . . . fails” by “the value -2 if the processor does
8 not support the concept of a command line. It is assigned a processor-dependent positive value if the
9 command retrieval fails for any other reason”.]

10 [Editor: Within the STATUS argument paragraph of **13.7.4.2 GET_COMMAND_ARGUMENT (NUM- 318:6**
11 **BER[, VALUE, LENGTH, STATUS])**, insert “It is assigned the value -2 if NUMBER is negative or
12 greater than the number of command arguments. It is assigned the value -3 if the processor does not
13 support the concept of a command line.” after “NUMBER.” Insert “for any other reason” after “fails”.]