Subject: Module variables and common retain state
From: Van Snyder

1 Edits

Edits refer to 06-007r1. Page and line numbers are displayed in the margin. Absent other instructions, a page and line number or line number range implies all of the indicated text is to be replaced by associated text, while a page and line number followed by + (-) indicates that associated text is to be inserted after (before) the indicated line. Remarks are noted in the margin, or appear between [and] in the text.

[Editor: Delete "If ... finalized.".]	71:20-21
[Editor: "occurs" ⇒ "is declared in". Insert ", a module, or a submodule" after "main program". Delete A variable in module ... submodule".]	72:3+2-5
[Editor: Insert ", a module, or a submodule" after "main program" thrice.]	97:27-98:2
[Editor: Insert "or is declared in the main program, a module, or a submodule" after "attribute".]	113:10
[Editor: Delete the paragraph "If ... deallocated."]	130:13-15
[Editor: Delete Note 6.30.]	130:15+1 etc.
[Editor: Replace "appears" by "is declared", insert "in the main program, a module, a submodule, or".]	493:19
[Editor: Delete items (7)(d) and (7)(e).]	493:21-24
[Editor: Insert "the common block is declared in the main program, a module, a submodule, or" after "unless".]	501:39
[Editor: Delete item (3)(c) and Note 16.19.]	501:41-42+6
[Editor: Delete item (3)(d).]	502:1-3