Subject: Get more information if GET_COMMAND or GET_COMMAND_ARGUMENT fails
From: Van Snyder
Reference: 03-258r1, section 2.3.2, 04-170, 04-381, WG5/N1626-J3-012

1 Edits

Edits refer to 04-007. Page and line numbers are displayed in the margin. Absent other instructions, a page and line number or line number range implies all of the indicated text is to be replaced by associated text, while a page and line number followed by + (-) indicates that associated text is to be inserted after (before) the indicated line. Remarks are noted in the margin, or appear between [and] in the text.

[Editor: Within the STATUS argument paragraph of **13.7.4.1 GET_COMMAND ([COMMAND, LENGTH, STATUS])**, replace "a processor-dependent ... fails" by "the value −2 if the processor does not support the concept of a command line. It is assigned a processor-dependent positive value if the command retrieval fails for any other reason".] 317:17

[Editor: Within the STATUS argument paragraph of **13.7.4.2 GET_COMMAND_ARGUMENT (NUMBER[, VALUE, LENGTH, STATUS])**, insert "It is assigned the value −2 if NUMBER is negative or greater than the number of command arguments. It is assigned the value −3 if the processor does not support the concept of a command line." after "NUMBER." Insert "for any other reason" after "fails".] 318:6